

**CERT**

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DW-8211CQ0578Registration Number
Registriernummer**Field of Application**
*Anwendungsbereich*products of water supply
*Produkte der Wasserversorgung***Owner of Certificate**
*Zertifikatinhaber*Valsir S.p.A.
Loc. Merlaro, 2, I-25078 Vestone (BS)**Distributor**
*Vertreiber*Valsir S.p.A.
Loc. Merlaro, 2, I-25078 Vestone (BS)**Product Category**
*Produktart*composite tubes for drinking water installations: PE-Xb/Al/PE-HD tube
(8211)**Product Description**
Produktbezeichnung

PE-Xb/Al/PE-HD tube, manufacturing group 1

Model
Modell

MIXAL

Test Reports
*Prüfberichte*type testing: 151005DK from 05.10.2015 (KIW)
hygienic testing: MO 165/16 from 16.08.2016 (TZW)
KTW testing: KR 145/15 from 28.07.2015 (TZW)**Test Basis**
*Prüfgrundlagen*DVGW W 542 (01.08.2009)
UBA KTW (07.10.2008)
DVGW W 270 (01.11.2007)**Date of Expiry / File No.** 05.10.2020 / 15-0663-WNE
Ablaufdatum / Aktenzeichen

08.09.2016 GI A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 for certification of products for energy and water supply industry.

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte Stelle für die Zertifizierung von Produkten der Energie- und Wasserversorgung.

Deutsche
Akkreditierungsstelle
D-ZE-16028-01-05DVGW CERT GmbH
ZertifizierungsstelleJosef-Wirmer-Str. 1-3
53123 BonnTel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993www.dvgw-cert.com
info@dvgw-cert.com

Tubi multistrato metallo-plastici per adduzione di acqua potabile calda e fredda (DVGW W542, KTW, W270).
Metal-plastic multi-layer pipes for transporting hot and cold drinking water (DVGW W542, KTW, W270).

A-2/2

DW-8211CQ0578

Type	Technical Data	Remarks
Typ	Technische Daten	Bemerkungen
MIXAL	manufacturing group: 1	diameters: up to 63 mm

Hints of Utilization / Remarks**Verwendungshinweise / Bemerkungen**

tested diameters: 16,0 x 2,00 mm (Al: 0,20 mm), 20,0 x 2,00 mm (Al: 0,20 mm), 26,0 x 3,00 mm (Al: 0,35 mm),
32,0 x 3,00 mm (Al: 0,40 mm)

valsisir®

DVGW